

GENERAL PURPOSE SILICON RECTIFIER


<p>FEATURES</p> <ul style="list-style-type: none"> • Low cost construction • Low forward voltage drop • Low reverse leakage • High forward surge current capability • High temperature soldering guaranteed: 260°C/10 seconds/0.375" (9.5mm) lead length at 5 lbs (2,3kg) tension <p>MECHANICAL DATA</p> <ul style="list-style-type: none"> • Case: Transfer molded plastic • Epoxy: UL94V-0 rate flame retardant • Polarity: Color band denotes cathode end • Lead: Plated axial lead, solderable per MIL-STD-202E method 208C • Mounting position: Any • Weight: 0.042 ounce, 1.19 grams 	<p>VOLTAGE RANGE 50 to 1000 Volts CURRENT 3.0 Ampere</p>  <p style="text-align: right;">DO-27</p> <p style="text-align: center;">Dimensions in inches and (millimeters)</p>																																																																																																																																
<p>MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS</p> <p>Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load derate current by 20%.</p>																																																																																																																																	
	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>SYMBOLS</th> <th>IN 5400</th> <th>IN 5401</th> <th>IN 5402</th> <th>IN 5404</th> <th>IN 5406</th> <th>IN 5407</th> <th>IN 5408</th> <th>UNITS</th> </tr> </thead> <tbody> <tr> <td>Maximum Repetitive Peak Reverse Voltage</td> <td>V_{RRM}</td> <td>50</td> <td>100</td> <td>200</td> <td>400</td> <td>600</td> <td>800</td> <td>1000</td> <td>Volts</td> </tr> <tr> <td>Maximum RMS Voltage</td> <td>V_{RMS}</td> <td>35</td> <td>70</td> <td>140</td> <td>280</td> <td>420</td> <td>560</td> <td>700</td> <td>Volts</td> </tr> <tr> <td>Maximum DC Blocking Voltage</td> <td>V_{DC}</td> <td>50</td> <td>100</td> <td>200</td> <td>400</td> <td>600</td> <td>800</td> <td>1000</td> <td>Volts</td> </tr> <tr> <td>Maximum Average Forward Rectified Current 0.5" (12.5mm) lead length at $T_L=105^\circ C$</td> <td>$I_{(AV)}$</td> <td colspan="7" style="text-align: center;">3.0</td> <td>Amps</td> </tr> <tr> <td>Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)</td> <td>I_{FSM}</td> <td colspan="7" style="text-align: center;">200</td> <td>Amps</td> </tr> <tr> <td>Maximum Instantaneous Forward Voltage at 3.0A</td> <td>V_F</td> <td colspan="7" style="text-align: center;">1.0</td> <td>Volts</td> </tr> <tr> <td rowspan="2">Maximum DC Reverse Current at rated DC blocking voltage</td> <td>$T_A=25^\circ C$</td> <td colspan="7" style="text-align: center;">10</td> <td rowspan="2" style="text-align: center;">μAmps</td> </tr> <tr> <td>$T_A=150^\circ C$</td> <td colspan="7" style="text-align: center;">500</td> </tr> <tr> <td>Maximum Full Load Reverse Current, full cycle average 0.5" (12.5mm) lead length at $T_L=105^\circ C$</td> <td>$I_{R(AV)}$</td> <td colspan="7" style="text-align: center;">500</td> <td>μAmps</td> </tr> <tr> <td>Typical Junction Capacitance(NOTE1)</td> <td>C_J</td> <td colspan="7" style="text-align: center;">40</td> <td>pF</td> </tr> <tr> <td>Typical Thermal Resistance(NOTE2)</td> <td>$R_{\theta JA}$</td> <td colspan="7" style="text-align: center;">30</td> <td>°C/W</td> </tr> <tr> <td>Operating and Storage Temperature Range</td> <td>T_J, T_{STG}</td> <td colspan="7" style="text-align: center;">-65 to +175</td> <td>°C</td> </tr> </tbody> </table>		SYMBOLS	IN 5400	IN 5401	IN 5402	IN 5404	IN 5406	IN 5407	IN 5408	UNITS	Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts	Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts	Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts	Maximum Average Forward Rectified Current 0.5" (12.5mm) lead length at $T_L=105^\circ C$	$I_{(AV)}$	3.0							Amps	Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	200							Amps	Maximum Instantaneous Forward Voltage at 3.0A	V_F	1.0							Volts	Maximum DC Reverse Current at rated DC blocking voltage	$T_A=25^\circ C$	10							μAmps	$T_A=150^\circ C$	500							Maximum Full Load Reverse Current, full cycle average 0.5" (12.5mm) lead length at $T_L=105^\circ C$	$I_{R(AV)}$	500							μAmps	Typical Junction Capacitance(NOTE1)	C_J	40							pF	Typical Thermal Resistance(NOTE2)	$R_{\theta JA}$	30							°C/W	Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +175							°C
	SYMBOLS	IN 5400	IN 5401	IN 5402	IN 5404	IN 5406	IN 5407	IN 5408	UNITS																																																																																																																								
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts																																																																																																																								
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts																																																																																																																								
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts																																																																																																																								
Maximum Average Forward Rectified Current 0.5" (12.5mm) lead length at $T_L=105^\circ C$	$I_{(AV)}$	3.0							Amps																																																																																																																								
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	200							Amps																																																																																																																								
Maximum Instantaneous Forward Voltage at 3.0A	V_F	1.0							Volts																																																																																																																								
Maximum DC Reverse Current at rated DC blocking voltage	$T_A=25^\circ C$	10							μAmps																																																																																																																								
	$T_A=150^\circ C$	500																																																																																																																															
Maximum Full Load Reverse Current, full cycle average 0.5" (12.5mm) lead length at $T_L=105^\circ C$	$I_{R(AV)}$	500							μAmps																																																																																																																								
Typical Junction Capacitance(NOTE1)	C_J	40							pF																																																																																																																								
Typical Thermal Resistance(NOTE2)	$R_{\theta JA}$	30							°C/W																																																																																																																								
Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +175							°C																																																																																																																								
<p>NOTES:</p> <p>1. Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts. 2. Thermal Resistance from Junction to Ambient at 0.5" (12.5mm) lead length, P.C. board mounted with 0.8" X 0.8" (20.0X20.0mm) copper heatsink.</p>																																																																																																																																	

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

