

Technical Specifications

APC Back-UPS 350VA X545 230V | BK350EIX545 | Downloaded on 08/01/2019 (EST)

Life Is On  APC
by Schneider Electric



APC Back-UPS 350VA X545 230V

BK350EIX545

Call for More Information 800-800-4272

- Best Value Battery Backup & Protection for Business Computers
- Includes: Qty 2 - Detachable IEC C13 to IEC C14 power cords

Output

Output power capacity	210Watts / 350VA
Max Configurable Power (Watts)	210Watts / 350VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Topology	Standby
Waveform type	Stepped approximation to a sinewave
Output Connections	(3) NEMA 5-15R (selector_surgetitle) (3) NEMA 5-15R (Battery Backup)
Transfer Time	6ms typical : 10ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input voltage range for main operations	196 - 280V

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6hour(s)
Replacement Battery	RBC2 

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Back-UPS 350VA X545 230V | BK350EIX545 | Downloaded on 08/01/2019 (EST)

Batteries & Runtime

Expected Battery Life (years)	4 - 6
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management

Interface Port(s)	DB-9 RS-232, USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators

Surge Protection and Filtering

Surge energy rating	300Joules
Data Line Protection	RJ-45 Modem/Fax protection (two wire single line)
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	6.5inches (165MM, 16.5CM)
Maximum Width	3.6inches (91MM, 9.1CM)
Maximum Depth	11.2inches (284MM, 28.4CM)
Net Weight	12.5lbs. (5.68KG)
Shipping weight	14.0lbs. (6.36KG)
Shipping Height	10.35inches (263MM, 26.3CM)
Shipping Width	6.89inches (175MM, 17.5CM)
Shipping Depth	14.06inches (357MM, 35.7CM)
Color	Beige
Master Carton Units	2.0
Master Carton Weight	14.0lbs. (6.36)
Units per Pallet	48.0
SCC Codes	1073130426028 5

Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
-----------------------	-------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Back-UPS 350VA X545 230V | BK350EIX545 | Downloaded on 08/01/2019 (EST)

Environmental	
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	20.0BTU/hr

Conformance	
Approvals	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE
Equipment protection policy	Lifetime : 100000 Euro, Lifetime : 50000 GBP
Standard warranty	2 years repair or replace

Sustainable Offer Status	
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.